

CYCLE 2017-07

List of new items – first version

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<

CN code	TARIC	Reference Mail	Description	S/Q	New or amendment request	Public Comments
2712 20 90		5503506/2016	Paraffin wax containing by weight less than 0,75 % of oil	Q/8500tonnes, 01.07-31.12	New	ROUND 2017-07 Paraffin wax is used as candle fuel, either exclusively or in mixtures with other fuels.
2712 20 90		5503608/2016	Paraffin wax containing by weight less than 0,75 % of oil	Q/3500tonnes, 01.07-31.12	New	ROUND 2017-07Paraffin wax is used as candle fuel, either exclusively or in mixtures with other fuels.
2712 20 90		5503430/2016	Paraffin wax containing by weight less than 0,75 % of oil	Q/2300tonnes, 01.07-31.12	New	ROUND 2017-07Paraffin wax is used as candle fuel, either exclusively or in mixtures with other fuels.
2712 20 90		5503114/2016	Paraffin wax containing by weight less than 0,75 % of oil	Q/tonnes,	New	ROUND 2017-07Paraffin wax is used as candle fuel, either exclusively or in mixtures with other fuels
2712 20 90		5459963/2016	Paraffin wax containing by weight less than 0,75 % of oil	Q/138000tonnes, 01.07-31.12	New	ROUND 2017-07 Paraffin wax used to produce indoor and outdoor candles

2905 31 00		5555215/2016	Ethylene glycol (Ethanediol)	Q/214000tonnes, 01.07-31.12	New	Ethylene glycol is primarily used in antifreeze formulations and as a raw material in the manufacture of polyesters such as polyethylene terephthalate (PET). It is also used as coolant and heat transfer agent and antifreeze
2915 31 00		5582741/2016	Ethyl acetate (CAS RN 141-78-6)	Q/10849tonnes, 01.07-31.12	New	Used in the manufacture of inks and coatings
2932 12 00		5457221/2016	2-Furaldehyde (CAS RN 98-01-1)	Q/10000tonnes, 01.07-31.12	New	ROUND 2017-07 The main uses: downstream production a raw material used in the foundry industry; and (ii)solvent-refiner of lubricating oils
3824 90 92		5573365/2016	Mixtures containing : - 60 % or more but not more than 90 % by weight of 2-chloropropene (CAS RN 557-98-2), - 8 % or more but not more than 14 % by weight of (Z)-1-chloropropene (CAS RN 16136-84-8), - 5 % or more but not more than 23 % by weight of 2-chloropropane (CAS RN 75-29-6), - not more than 6 % by weight of 3-chloropropene (CAS RN 107-05-1) and, - not more than 1 % by weight of ethyl chloride (CAS RN 75-00-3)	Q/3000tonnes, 01.07-31.12	New	MCPe is used as a raw material in order to produce a chlorinated precursor. The latter is used as a solvent or a foam extension agent.
5505 10 10		5451208/2016	Waste of synthetic fibres (including noils, yarn waste and garnetted stock) in different lengths of nylon or other polyamides (PA6 und PA66)	Q/11000tonnes, 01.07-31.12	New	ROUND 2017-07 Endverwendung der Einfuhrware: Technischer Kunststoff für Automobil- und Bauindustrie
7601 10 10		5555177/2016	Unwrought aluminium, not alloyed	Q/385000tonnes, 01.07-31.12	New	Aluminium can be produced via two different routes - production of primary aluminium from bauxite ore and production of secondary aluminium from recycled process scrap and used aluminium products. Primary or secondary

						aluminium is used to produce semis such as flat rolled aluminium, cast aluminium, extrusion, wire rod and others. End products are used in sectors like transportation, building&construction, packaging, electrics&electronics, industrial products, consumer durables, defense and others
7601 20 20		5555303/2016	Unwrought aluminium, aluminium alloys – slabs and billets	Q/130000tonnes, 01.07-31.12	New	Aluminium can be produced via two different routes - production of primary aluminium from bauxite ore and production of secondary aluminium from recycled process scrap and used aluminium products. Primary or secondary aluminium is used to produce semis such as flat rolled aluminium, cast aluminium, extrusion, wire rod and others. End products are used in sectors like transportation, building&construction, packaging, electrics&electronics, industrial products, consumer durables, defense and others
7601 20 80		5555261/2016	Unwrought aluminium, aluminium alloys – other	Q/100000tonnes, 01.07-31.12	New	Aluminium can be produced via two different routes - production of primary aluminium from bauxite ore and production of secondary aluminium from recycled process scrap and used aluminium products. Primary or secondary aluminium is used to produce semis such as flat rolled aluminium, cast aluminium, extrusion, wire rod and others. End products are used in sectors like transportation, building&construction, packaging, electrics&electronics, industrial

						products, consumer durables, defense and others
8414 90 00		5572918/2016	Compressor wheel of a kind use for turbo-compressors in car manufacturing industry or other industrial applications: - manufactured from aluminum alloy - with a diameter of 20 millimeters or more, but not more than 130 millimeters - with a weight of 5 grams or more, but not more than 800 grams	Q/2950000pieces, 01.07-31.12	New	The machine which, through a turbine housing takes its energy from exhaust gases. and in the meantime compresses engine air used for combustion for a automotive vehicle, a truck, an off high way vehicle, a boat; etc...
8714 10 90		5501376/2016	Pistons for suspension systems of sintered steel according to standard ISO P2054 of a kind used for motor bikes	Q/2000000pieces, 01.07-31.12	New	ROUND 2017-07 articles for the production of motor bike suspension systems
2915 32 00		726215/2014 825537/2014 838627/2014 838774/2014 898981/2014	Vinyl acetate (CAS RN 108-05-4)	Q/225000tonnes, 01.01-30.06	Amendment	ROUND 2017 01 request for increase ROUND 2016-01 request for quota increase - rejected ROUND 2015-07 request for quota increase ROUND 2015-01-01 Vinyl Acetate Monomer can be polymerized, either by itself to make polyvinyl acetate or with other monomers to prepare copolymers such as ethylene-vinyl acetate en Ethylene-Vinyl Alcohol.
3905 30 00		137255/2010	Poly(vinyl alcohol), whether or not containing unhydrolysed acetate groups	Q/22500tonnes, 01.01-30.06	Amendment	ROUND 2016-01-01 A request to prolong the measure for the same amount (15 000t) ROUND 2014-07-01:A request to prolong the measure Proposal for 1/1/2014 round:

						Amended description: "Poly(vinyl alcohol), whether or not containing unhydrolysed acetate groups for use in the manufacture of adhesives falling within heading 3506"
ex 3907 40 00	25	706680/2014	Polymer blend of polycarbonate and poly(methyl methacrylate) with a polycarbonate content of not less than 98,5 % by weight, in the form of pellets or granules, with a luminous transmittance of not less than 88,5 %, measured using a test sample with a thickness of 4 mm at a wavelength of $\lambda = 400$ nm (according to ISO 13468-2)	Q/400tonnes, 01.01-31.12	Amendment	ROUND 2017-07 amendment request - request to increase quota ROUND 2016-01: rollover to correct mimor the text description as regards to %. ROUND 2015-07:Rollover / Resubmission from previous cycle ROUND 2015-01-01:>> Mode of operation:highly transparent polycarbonate with light-guiding properties >> Intended use:manufacture of optical systems, in particular light guidance and lenses, with low loss of transparency and very little colour shift over long light guiding distances (>300 mm) with feed of white LED light
ex 3911 90 19	10	1450/7/1995	Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene)	Q/5500tonnes, 01.01-31.12	Amendment	ROUND 2017 01:opposition Prolongation Exercise 1/1/2014
5504 10 00		1367832/2016	Artificial staple fibres of viscose rayon not carded, combed or otherwise processed for spinning	Q/148000tonnes,	Amendment	ROUND 2017-07 resubmission ROUND 2017 01 iscose, similar to cotton, is an artificial raw material of textiles, comprised of cellulose

7019 40 00 7019 52 00		1290020/2016	<p>12.5.16 UK proposal: Woven fabrics of glass filaments in rolls, weighing 15 g/m² or more but not more than 220 g/m² :</p> <ul style="list-style-type: none"> - of a width of 60 cm or more but not more than 160 cm, and - with a thickness of 0,020 mm or more but not more than 0,260 mm <p>for use in the manufacture of prepregs</p> <p>Fibreglass fabric</p> <ul style="list-style-type: none"> - E-glass filaments - (supplied) in rolls of a width of 60.0 cm or more, but not more than 160.0 cm, - with a fibreglass fabric thickness of 0.020 mm or more, but not more than 0.260 mm, - with a grammage of 15 g/m² or more, but not more than 220 g/m² 	Q/8530km, 01.01-31.12	Amendment	<p>ROUND 2017-07 resubmission</p> <p>ROUND 2017-01 Glasgewebe in Rollen</p>
ex 8302 49 00	91	912/2/2004	Aluminium telescopic handle for use in the manufacture of luggage	Q/1000000pieces, 01.01-31.12	Amendment	<p>ROUND 2017-07 request for increase</p> <p>QUO201507 request for increase</p> <p>TARIC code 7616 99 90 85 has been deleted as it was decided a classification under this code is wrong concerning the goods in question</p>
CN code	TARIC	Reference Mail	Description	S/Q	New or amendment request	Public Comments
2825 70 00		5559884/2016	Molybdic Acid (CAS RN 7782-91-4)	S	New	Molybdic acid. Powder in big bag. Raw material of chemical reaction to produce an organometallic salt

						used as catalyst for oil industry. Final product HS code: 29 15 90 70
2904 20 00		5501233/2016	4-Methoxy-5-(3-morpholin-4-yl-propoxy)-2-nitro-benzonitrile (CAS RN 675126-26-8)	S	New	ROUND 2017-07 used for the production of active pharmaceutical substances
2905 22 00		5450710/2016	3,7-Dimethyloct-6-en-1-ol (CAS RN 106-22-9)	S	New	ROUND 2017-07 Einsatz als Duftstoff; Zwischenprodukt für die Herstellung von Citronellylacetat
ex 2905 39 95	20	5501275/2016	Butane-1,2-diol (CAS RN 584-03-2)	S	New	ROUND 2017-07 The product is used for the production of an antibiotic
2909 19 90		5531326/2016	((2,2-dimethylbut-3-yn-1-yl)oxy)methylbenzene	S	New	Product used in the manufacturing of a new Active Pharmaceutical Ingredient.
2909 30 90		5450733/2016	1,2-Diphenoxyethane (CAS RN 104-66-5)	S	New	ROUND 2017-07 Reaktionsbeschleuniger für Thermopapiere
2912 19 00		5450756/2016	Undecanal (CAS RN 112-44-7)	S	New	ROUND 2017-07 Rohstoff/Zwischenprodukt zur Herstellung eines Riechstoffes
2916 12 00		5460155/2016	Oxybis(methyl-2,1-ethanediy)l diacrylate (CAS RN 57472-68-1)	S	New	ROUND 2017-07 reactive resin used in formulation for UV curing processes for coatings, inks and adhesives
2916 12 00		5459999/2016	2-Acryloyloxymethyl-2-ethyltrimethylene diacrylate (CAS RN 15625-89-5)	S	New	ROUND 2017-07 reactive resin used in formulation for UV curing processes for coatings, inks and adhesives

2916 12 00	5460042/2016	Hexamethylene diacrylate (CAS RN 13048-33-4)	S	New	ROUND 2017-07 reactive resin used in formulation for UV curing processes for coatings, inks and adhesives
2916 39 90	5552271/2016	methyl 4'-(bromomethyl)biphenyl-2-carboxylate	S	New	It is used to manufacture the API Telmisartan at the manufacturing plant of Interquim (Spain)
2917 20 00	5654291/2016	1,2-Cyclohexanedicarboxylic acid, 1-butyl 2-(phenylmethyl) ester (CAS RN 1200806-67-2)	S	New	Liquid plasticiser
2918 99 90	5450776/2016	(2,4-Dichlorophenyl)acetyl chloride (CAS RN 53056-20-5)	S	New	ROUND 2017-07 raw material used in the production of crop protection active ingredient
2919 90 00	5652420/2016	Isodecyl diphenyl phosphate (CAS RN 29761-21-5)	S	New	Primary flame retarding plasticiser for PVC, Coatings, Adhesives, Sealants
2922 19 85	5531479/2016	(R)-1-((4-amino-2-bromo-5-fluorophenyl)amino)-3-(benzyloxy)propan-2-ol 4-methylbenzenesulfonate	S	New	Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity)
2924 29 98	5450799/2016	Sodium 4-(4-methyl-3-nitrobenzoylamino)benzenesulphonate (CAS RN 84029-45-8)	S	New	ROUND 2017-07 Farbmittel für Farben-, Druckfarben- und Lackindustrie
2924 29 98	5227004/2016	N-benzyloxycarbonyl-l-tert-leucina isopropylamine salt (CAS RN 1621085-33-3)	S	New	ROUND 2017-07 raw material for the synthesis of pharmaceutical used to treat infection of human immunodeficiency virus
2926 90 95	5501295/2016	4-Methoxy-3-(3-morpholin-4-yl-propoxy)-benzonitrile (CAS RN 675126-28-0), whether or not in organic solvents	S	New	ROUND 2017-07 used for the production of active pharmaceutical substances
2926 90 95	5572875/2016	4,5-dichloro-3,6-dioxocyclohexa-1,4-diene-1,2-dicarbonitrile (CAS RN 84-58-2)	S	New	Chemical intermediate for the manufacture of

2930 90 99	5573326/2016	Mixture of isomers of 1-(tert-dodecylthio)propan-2-ol (CAS RN 67124-09-8)	S	New	pharmaceutical active ingredient ROUND 2017-07 The product is an ashless oxidation inhibitor used in automatic transmission fluids
2932 99 00	5572888/2016	(4-chloro-3-(4-ethoxybenzyl)phenyl)((3aS,5R,6S,6aS)-6-hydroxy-2,2-dimethyltetrahydrofuro[2,3-d][1,3]dioxol-5-yl)methanone (CAS RN 1103738-30-2)	S	New	Chemical intermediate for the manufacture of pharmaceutical active ingredient
2932 99 00	5531421/2016	4-(4-bromo-3-((tetrahydro-2H-pyran-2-yloxy)methyl)phenoxy)benzotrile	S	New	Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity)
2933 19 90	5552079/2016	5-methyl-1-(naphthalen-2-yl)-1H-pyrazol-3-ol	S	New	Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity)
2933 19 90	5450826/2016	5-Amino-1-[2,6-dichloro-4-(trifluoromethyl)phenyl]-1H-pyrazole-3-carbonitrile (CAS RN 120068-79-3)	S	New	ROUND 2017-07 product used in production of pesticides
2933 29 90	5450845/2016	2,2'-Azobis[2-(2-imidazolin-2-yl)propane] dihydrochloride (CAS RN 27776-21-2)	S	New	ROUND 2017-07 Endverwendung der Einfuhrware: Polymerisationsinitiator in der Superabsorber-Produktion
2933 39 99	5552155/2016	2-chloro-6-(3-fluoro-5-isobutoxyphenyl)nicotinic acid	S	New	Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity)

2933 39 99		5450881/2016	Fluopicolide (ISO) (CAS RN 239110-15-7)	S	New	ROUND 2017-07 Wirkstoff in einem Pflanzenschutzmittel
2933 39 99		5552032/2016	5-(3-chlorophenyl)-3-methoxypyridine-2-carbonitrile	S	New	Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity)
2933 39 99		5552224/2016	2-aminopyridin-4-ol hydrochloride	S	New	Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity)
2933 99 80		5531366/2016	(2S,3S,4R)-methyl 3-ethyl-4-hydroxypyrrolidine-2-carboxylate 4-methylbenzenesulfonate	S	New	Product used in the manufacturing of a new Active Pharmaceutical Ingredient
2933 99 80		5450905/2016	Tivantinib (INN) (CAS RN 905854-02-6)	S	New	ROUND 2017-07 End use of the imported goods: Production of tablets - Medicaments
2933 99 80		5531531/2016	3-chloro-2-(1,1-difluorobut-3-enyl)-6-methoxyquinoxaline	S	New	Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity)
2933 99 80		5552188/2016	(S)-2,2,4-trimethylpyrrolidine hydrochloride	S	New	Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity)
2934 99 90		5552312/2016	Cytidine 5'-monophosphate disodium salt	S	New	It is used as API to manufacture the pharmaceutical product Nucleo CMP forte capsules and injectable
2934 99 90		5450922/2016	Thidiazuron (ISO) (CAS RN 51707-55-2)	S	New	ROUND 2017-07 Endverwendung der Einfuhrware: Zubereitete Pflanzenschutzmittel

2935 00 90		5552111/2016	6-aminopyridine-2-sulfonamide	S	New	Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity)
3204 17 00		5582640/2016	Colourant C.I. Pigment Red 57:1 (CAS RN 5281-04-9) and preparations based thereon with a Colourant C.I. Pigment Red 57:1 content of 50 % or more by weight	S	New	Used in the manufacture of inks and coatings
3204 17 00		5582590/2016	Colourant C.I. Pigment Red 169 (CAS RN 12237-63-7) and preparations based thereon with a Colourant C.I. Pigment Red 169 content of 50 % or more by weight	S	New	Used in the manufacture of inks and coatings
3811 21 00		5573295/2016	Dispersing agent and oxidation inhibitor containing : -o-amino polyisobutylenephenol (CAS RN 78330-13-9), -more than 30 % by weight but not more than 50 % by weight of mineral oils, used in the manufacture of blends of additives for lubricating oils	S	New	The product is a dispersant and oxidation inhibitor specifically developed for use in two stroke engine lubricants
3811 21 00		5572847/2016	Detergent containing: - calcium long chain alkyltoluenesulphonates, - calcium borate and - more than 10 % but not more than 40 % by weight of mineral oils, used in the manufacture of blends of additives for lubricating oils	S	New	This is a detergent additive, which is blended with other chemical products to make lubricating engine oils to prevent deposits and varnish formation and corrosion by neutralizing the acids formed during fuel combustion or oil oxidation

3811 21 00		5573482/2016	Detergent containing : -a magnesium salt of tetrapropylphenol and formaldehyde polymer, -more than 40 % by weight but not more of 60 % by weight of mineral oil, having a total base number of more than 40 but not more than 100, for use in the manufacture of blends of additives for lubricating oils	S	New	The product is a sulphur free phenate
3811 90 00		5572943/2016	Corrosion inhibitor containing : -polyisobutenyl succinic acid and -more than 5 % and not more than 20 % by weight of mineral oils. used in the manufacture of blends of additives for fuels	S	New	Corrosion inhibitor
3812 20 90		5654225/2016	1,2-benzenedicarboxylic acid, benzyl C7-9-branched and linear alkyl esters (CAS RN 68515-40-2)	S	New	Liquid plasticiser
3824 90 92		5460118/2016	Poly[oxy(methyl-1,2-ethanediyl)], $\alpha, \alpha', \alpha''$ -1,2,3-propanetriyltris[ω -[(1-oxo-2-propen-1-yl)oxy]- (CAS RN 52408-84-1)	S	New	ROUND 2017-07 reactive resin used in formulation for UV curing processes for coatings, inks and adhesives
3824 90 92		5460258/2016	Poly(oxy-1,2-ethanediyl), α -hydro- ω -[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol, reaction	S	New	ROUND 2017-07 reactive resin used in formulation for UV curing processes for coatings, inks

			product with 2-amino-ethanol (CAS RN 188012-57-9)			and adhesives
3824 90 92		5582909/2016	Aqueous solution of caesium formate and potassium formate containing by weight: <ul style="list-style-type: none"> - 1 % or more but not more than 84 % of caesium formate (CAS RN 3495-36-1), and - 1 % or more but not more than 75 % of potassium formate (CAS RN 590-29-4) with a density range of 1.57 sg or more but not more than 2.2 sg	S	New	Caesium potassium formate brine is an aqueous solution of alkali metal salts of formic acid
3824 90 92		5651680/2016	Aqueous solution containing by weight 60 % or more but not more than 84 % of caesium formate	S	New	Aqueous cesium formate is intended for use in the development of oil and natural gas wells.
3824 90 92		5651724/2016	Aqueous solution of caesium formate and potassium formate containing by weight: <ul style="list-style-type: none"> - 1 % or more but not more than 84 % of caesium formate (CAS RN 3495-36-1), and - 1 % or more but not more than 76 % of potassium formate (CAS RN 590-24-1) 	S	New	Aqueous solution of caesium formate and potassium formate is intended for use in the development of oil and natural gas wells.
3824 90 92		5654333/2016	Preparation containing by weight: <ul style="list-style-type: none"> - 25 % or more but not more than of diethyl carbonate (CAS RN 105-58-8) - 25 % or more but not more than 50 % of ethylene carbonate (CAS RN 96-49-1) - 10 % or more but not more than 20 % of lithium hexafluorophosphate (CAS RN 21324-40-3) - 5 % or more but not more than 10 % of ethyl methyl carbonate (CAS RN 623-53-0) - 1 % or more but not more than 2 % of vinylene carbonate (CAS RN 872-36-6) - 1 % or more but not more than 2 % of 4-fluoro-1,3-dioxolane-2-one (CAS RN 114435-02-8) 	S	New	Formulated electrolyte for lithium-ion batteries

3824 90 93	5505061/2016	<p>- Not more than 1 % of 1,5,2,4-Dioxadithiane 2,2,4,4-tetraoxide (CAS RN 99591-74-9)</p> <p>Sodium hydrogen 3-aminonaphthalene-1,5-disulfonate containing by weight:</p> <ul style="list-style-type: none"> - not more than 20 % of disodium sulphate, and - not more than 10 % of sodium chloride 	S	New	ROUND 2017-07 Raw material for production of other chemical compounds
3824 90 96	5501338/2016	<p>Mixture consisting of:</p> <ul style="list-style-type: none"> - 64 % or more, but not more than 74 % by weight of by weight of amorphous silica (CAS RN 7631-86-9) - 25 % or more, but not more than 35 % by weight of butanone (CAS RN 78-93-3) and - not more than 1 % by weight of 3-(2,3-epoxypropoxy)propyltrimethoxysilane (CAS RN 2530-83-8) 	S	New	ROUND 2017-07 production of prepregs
3824 90 96	5582818/2016	<p>Powder containing by weight:</p> <ul style="list-style-type: none"> • 28 % or more but not more than 32 % of talc • 43 % or more but not more than 48 % of silicon dioxide (quartz) • 22 % or more but not more than 26 % of aluminium oxide <p>[for use in the manufacture of U-type glass fibre]</p>	S	New	For use in the manufacture of glass fibre
3824 90 96	5582854/2016	<p>Powder containing by weight:</p> <ul style="list-style-type: none"> • 46 % or more but not more than 51 % of talc • 30.5 % or more but not more than 34.5 % of silicon dioxide (quartz) • 17.5 % or more but not more than 	S	New	For use in the manufacture of glass fibre

			20.5 % of aluminium oxide [for use in the manufacture of K-type glass fibre]			
3905 30 00	5451094/2016		With acetoacetate groups modified poly (vinyl alcohol), containing non-hydrolyzed acetyl groups [for the production of thermal paper]	S	New	ROUND 2017-07 Endverwendung der Einfuhrware: Veredelung von Papier
3906 90 90	5451123/2016		Copolymer of butyl acrylate, methyl methacrylate and dimethylsiloxane (CAS RN 143106-82-5) [in form of a white powder]	S	New	ROUND 2017-07 Vorgesehene Verwendung Schlagzähmodifikator für Polycarbonat
3906 90 90	5457188/2016		Polyacrylamide powder having an average particle size of less than 2 microns and a melting point of more than 260°C, containing by weight: - 15 % or more but not more than 25 % of polyethylene glycol - [not more than 2 % of methanol]	S	New	ROUND 2017-07 heat stabilizer
3910 00 00	5651807/2016		Dimethyl Siloxane, Hydroxy-terminated polymer with a viscosity: 38-45 mPa.s (CAS RN 70131-67-8)	S	New	Material in the synthesis of siloxanes and silicone rubber
3910 00 00	5651745/2016		Dimethyl Siloxane, Hydroxy-terminated polymer with a viscosity of 2000 mPa.s	S	New	Pulpaid antifoams; sealants; coatings
3910 00 00	5652366/2016		Preparation containing by weight: - 55 % or more but not more than 65 % of Vinyl terminated polydimethylsiloxane (CAS RN 68083-19-2), - 30 % or more but not more than 40 % of Dimethylvinylated and	S	New	Used to formulate paper coatings

			<p>trimethylated silica (CAS RN 68988-89-6),</p> <ul style="list-style-type: none"> - 1 % or more but not more than 5 % of Silicic acid, Sodium salt, reaction products with Chlorotrimethylsilane and Isopropyl alcohol (CAS RN 68988-56-7) 			
3910 00 00	5654370/2016	Vinyl Terminated Polydimethyl Siloxane with a Newtonian viscosity of 7 000 - 12 000 cP	S	New	Formulation ingredient	
3919 90 00	5451151/2016	Reinigungsfolie, bestehend aus einer Polymerschicht mit eingearbeiteten Schleifpartikel auf einem Substrat, zur Verwendung beim Reinigungsprozess von Messnadeln bei der Halbleiterherstellung	S	New	ROUND 2017-07 Endverwendung der Einfuhrware: Reinigung von Messnadeln auf Nadelkarten, welche beim Funktionstest von Halbleiterwafers Anwendung finden	
3920 99 59	5451174/2016	Folie aus Ethylen-Tetrafluorethylen in Rollen mit einer Dicke von 50 µm, einem Schmelzpunkt von 260° C und einer spezifischen Dichte von 1,75 (bezogen auf Wasser bei einer Temperatur von 4°C, bestimmt nach der Norm ASTM D792)	S	New	ROUND 2017-07 Vorgesehene Verwendung: Einsatz im Transfermold-Prozess bei der Herstellung von Halbleiterbauelementen	
3921 90 60	5457200/2016	<p>Porous Membrane of polytetrafluorethylene (PTFE) laminated to a polyester spunbonded non-woven cloth with</p> <ul style="list-style-type: none"> - a total thickness of more than 0,05mm but not more than 0,20 mm. - [a water entry pressure between 5 and 200 kPa according to the ISO 811 test method], - [an air permeability of 0,08 cm³/cm²/s or more according to the ISO 5636-5 test method] 	S	New	ROUND 2017-07 End application: used for lighting systems in automotive industry.	

3926 90 97		5560026/2016	Silicon decoupling ring, with an inner diameter of 15,4 mm (+0,0/-0,1), of a kind used in car parking aid sensor systems	S	New	Decoupling rings are assembled in our European plants on automated lines with other mechanical and electronics components. They contribute to the manufacturing of sensors used in automotive driving assistance systems, mainly for park assist (ULS - Ultrasonic Parking Sensor) . These systems are integrated by automotive manufacturers in most of their models in Europe and world wide. Decoupling rings provide sealing and insulating functions to protect the sensor from external vibrations; these external vibrations could disturb the quality and accuracy of the sensor output
4016 99 57		5524327/2016	Rubber bumper seal with a silicone coating of a length not more than 1 200 mm and with at least five plastic clips for use in the manufacture of goods of Chapter 87	S	New	Rubber bumper seal is mounted on the front bumper of passenger vehicle at the separate stand within the production line by the following processing
4016 99 57		5524428/2016	Air intake hose for air supply to the combustion part of the engine made at least of: <ul style="list-style-type: none"> - one flexible rubber hose; - metal clips; - whether or not of a resonator for use in the manufacture of goods of Chapter 87	S	New	The air intake hose is mounted to the front axle of a passenger car

7609 00 00		5457584/2016	Exhaust gas recirculation (EGR) valve tube made of aluminium alloy complying with standard EN-1706-AC-47100D	S	New	ROUND 2017-07 components of the exhaust gas recirculation valves of automotive vehicle engines
7616 99 10		5457613/2016	Exhaust gas recirculation (EGR) valve housing made of aluminium alloy complying with standard EN-1706-AC-44300D or EN-1706-AC-47100D	S	New	ROUND 2017-07 component of the exhaust gas recirculation valves of automotive vehicle engines
8409 99 00		5506673/2016	Plastic or aluminum cylinder head cover with <ul style="list-style-type: none"> - camshaft position sensor (CMPS), - inserts for counterparts assembly whether or not used for mounting wires, - metal brackets for mounting to engine, - two or more gaskets for use in the manufacture of engines of motor vehicles	S	New	ROUND 2017-07 Cylinder head cover - part of internal combustion piston engines of passenger car
8409 99 00		5506241/2016	Fuel hose for internal combustion piston engines with a fuel temperature sensor, with at least two inlet hoses and three outlet hoses for use in the manufacture of engines of motor vehicles	S	New	ROUND 2017-07 Fuel hose is a part of internal combustion piston engines of passenger car
8413 30 80		5506724/2016	High pressure pump for gasoline direct injection with operating pressure of 200 bar or more, but not more than 350 bar for use in the manufacture of engines of the motor vehicles	S	New	ROUND 2017-07 Gasoline direct injection high pressure pump - part of spark-ignition internal combustion piston engines of passenger car
8481 80 40		5506338/2016	Tyre valve with pressure measurement sensor in plastic housing for use in the manufacture of motor vehicles	S	New	ROUND 2017-07 Tyre pressure sensor - part of axle of the passenger car

8481 80 59		5505106/2016	Pressure regulating solenoid valve for incorporation into piston compressors of air conditioning machines of motor vehicles	S	New	ROUND 2017-07 Valve for incorporation into piston compressors of air conditioning machines of motor vehicles
8481 80 59		5505076/2016	Pressure regulating valve for incorporation into piston compressors of air conditioning machines of motor vehicles	S	New	ROUND 2017-07 Regulatory Valve based on input pressures in compressor changes and holds pressures in specific part of compressor.
8482 10 90		5572818/2016	Ball bearing bearing, using steel 102Cr6 : -having an outside diameter of 37mm, - having an internal diameter of 25mm, - supporting a maximum radial load of 4390N, - supporting an axial load of 2990N	S	New	The function of this ball bearing is to improve the opening and closing the shutter of the EGR valve
8482 10 90		5528937/2016	Ball bearings with an external diameter of 35 mm and an internal diameter of 15 mm and with a width of 11 mm. The outer ring has special grooves and the ball bearing contains special grease capable of withstanding a performance test in 30 degrees below zero Celsius. Specially made for the injection of plastic wheels	S	New	Plastic wheels
8484 20 00		5505154/2016	Shaft seal for incorporation into rotary compressors of air conditioning machines of motor vehicles	S	New	ROUND 2017-07 Shaft Seal is for incorporation into rotary compressors of air conditioning machines of motor vehicles
8501 10 99		5560070/2016	DC Motor : - with a speed rotation of 7000 rounds/minute (without load),	S	New	The function of this motor is to ensure the opening and closing the shutter of the EGR valve. It is

			<ul style="list-style-type: none"> - with a nominal voltage of 12V (+/- 4V), - with a maximum power of 13.78W (under 3.09A), - with a specified temperature range from -40° to 160°, - with a gear connection, - with a mechanical attachment interface - With 2 electrical connections, - with a maximum torque of 100N.M 			responsible for the recycling of exhaust gas
8501 10 99		5560106/2016	<p>DC Motor :</p> <ul style="list-style-type: none"> - with a speed rotation of 6500 rounds/minute (without load), - with a nominal voltage of 12V (+/- 4V), - with a maximal power below than 20 Watts, - with a specified temperature range from -40° to 160°, - with a worm gear drive - with a mechanical attachment interface - With 2 electrical connections, - with a maximum torque of 75N.M 	S	New	The function of this motor is to ensure the opening and closing the shutter of the Themis valve. It is responsible for the control and optimization of the water temperature of the engine
8504 50 95		5505747/2016	<p>Solenoid coil with;</p> <ul style="list-style-type: none"> - A rated power of more than 10 W but not more than 15 W, - An insulation resistance of 100 M Ohms or more, - A DC resistance of not more 34,8 Ohm (\pm % 10) at 20°C - A rated current of not more than 1,22 A, - A rated voltage of not more than 25 V 	S	New	ROUND 2017-07 used for production of Turkish Coffee Machine
8518 40 80		5523922/2016	<p>Audio power amplifier in a metal housing with</p> <ul style="list-style-type: none"> - 50 W of power, - a power supply of more than 9 V but not more than 16 V, - an electrical impedance not more than 4 Ohm, - a sensitivity more than 80 dB <p>for use in the manufacture of motor vehicles</p>	S	New	ROUND 2017-07 Audio power amplifier - part of dashboard of passenger car

8537 10 99		5524531/2016	Electronic immobilizer control unit with operating voltage of 9V or more, but not more than 16V, in a plastic housing, with a connector, whether or not with metal holder for use in the manufacture of goods of Chapter 87	S	New	The electronic immobilizer control unit is mounted to the dashboard of a passenger car
8537 10 99		5559923/2016	Lever : - with one or more single or multi-positional electrical switches (push-button, rotary or other), - whether or not equipped with printed circuit boards and electrical cables, - for a voltage of 9 V or more but not more than 16 V, for control module under the steering wheel, mounted on the steering column of motor vehicles of Chapter 87	S	New	The levers for controlling eg vehicle lighting, wipers and windshield washer, radio controls, cruise control, etc ... are assembled with other mechanical, electrical and/or electronic components on a supporting frame in our European factories on automatic or manual lines. The assembly thus created is complete equipment called Top Column Module (TCM). This TCM to be mounted in series by car manufacturers on the steering column of the motor vehicle is equipped with electrical contacts that connect to the vehicle's electrical system. All vehicles are equipped with TCM.
8537 10 99		5524483/2016	Control unit for keyless access and vehicle starting in plastic housing whether or not with: - an antenna, - a connector, - a metal holder for use in the manufacture of goods of Chapter 87	S	New	Control unit is mounted to the dashboard of passenger car

8538 90 99	5559994/2016	Front control panel, in the form of a plastic box, with light guides, rotary switches, pressure switches and buttons switches, or other type of switches, of a kind used in the dashboard of motor vehicles of Chapter 87	S	New	Round 2017-07 Front Panel: The Control Panel is designed to be mounted in series by car manufacturers on the dashboard of the motor vehicle. It is equipped with electrical contacts of devices that connect to the vehicle's electrical system.
8543 70 90	5451360/2016	Elektrochrome Folie; aus laminierten Folien mit zwei äußeren Lagen aus Polyester und einer Zwischenschicht aus Acrylpolymer und Silikon, sowie zwei elektrischen Anschlussklemmen	S	New	ROUND 2017-07 Einbau der elektrochromen Folien in die Glasdächer zweier Personalfahrzeuge zur Veränderung der Lichtdurchlässigkeit in den Innenraum des Automobils.
8544 42 90	5524595/2016	12-core connecting cable for voltage of 5V for connecting the control panel to the car radio or navigation, with length of not more than 300 mm and connectors on both ends for use in the manufacture of goods of Chapter 87	S	New	Extension cable is mounted to the dashboard of a passenger car
8706 00 91	5500085/2016	Set, containing various parts for a motor vehicle essentially designed to transport not more than six people, including: - A pipe chassis for a three wheeled vehicle (TukTuk) containing an electric driven motor and in general containing an instrument panel and various body work parts; - Roof and canvas - Roll bar - Wheels - Back seat	S	New	ROUND 2017-07 end-use of that product Electric motorvehicle mainly designed for transport of passengers
8707 10 10	5500056/2016	Body for an electric vehicle of 87039010, made wholly or in part of aluminium, equipped with among others:	S	New	ROUND 2017-07 Electric Vehicle Glider

8708 10 10 8708 10 90		5524180/2016	<ul style="list-style-type: none"> - Seats - 2 front wheels - Electrical equipment Steering wheel and dashboard	S	New	The plastic cover is mounted to the front bumper of a passenger car
8708 30 10 8708 30 91		5524249/2016	Connecting rod of the master brake cylinder with screw threads on both ends for use in the manufacture of goods of Chapter 87	S	New	The operative connecting rod is mounted to the master brake cylinder of a passenger car.
8708 80 20 8708 80 55		5524137/2016	Stabilizer bar of the front axle, mounted on both ends with a ball pivot for use in the manufacture of goods of Chapter 87	S	New	The stabilizer bar is mounted to the front axle of a passenger car. The installation must be performed in a dust-free zone since dirt cannot ingress to the casing.
8708 91 20 8708 91 99		5524287/2016	Front radiator holder whether or not with rubber cushioning for use in the manufacture of goods of Chapter 87	S	New	Holder is mounted to the front module of a passenger car
8708 99 10 8708 99 97		5524655/2016	Support bracket with mounting holes, whether or not with fixation nuts, for connecting the gearbox to the car body for use in the manufacture of goods of Chapter 87	S	New	The support bracket is mounted to gearbox case on the front axle of a passenger car

9025 80 40		5451321/2016	<p>Barometer, in combination with other instruments, substantially consisting of:</p> <ul style="list-style-type: none"> - a combination of one or more custom designed monolithic integrated circuits (ASIC) and - at least one or more micro mechanic sensor element(s) (MEMS) with mechanic elements manufactured in semiconductor technology <p>ASIC and MEMS are mounted on top of each other in stack technology (stacked)</p>	S	New	<p>ROUND 2017-07</p> <p>Endverwendung der Einfuhrware: Messung des barometrischen Luftdruckes und der Temperatur</p>
ex 2519 90 10	10	254871/2011	<p>Fused magnesia with a purity by weight of 94 % or more"</p> <p>--- PL - Mar 2016 ---</p>	S	Amendment	<p>ROUND 2017 01</p> <p>amending request (reducing purity)</p> <p>Prolongation Exercise 2017-01-01</p>
ex 2905 11 00	10	3090865/2013	<p>Fused magnesia with a purity by weight of 97 % or more</p> <p>Methanol (CAS RN 67-56-1) with a purity of 99,85 % by weight or more (as determined by the metanol purity method IMPCA 001-14) TR 15-09-2016</p> <p>Methanol (CAS RN 67-56-1) with a purity of 99,85 % by weight or more</p>	S	Amendment	<p>ROUND 2017-07</p> <p>amendment request</p> <p>ROUND 2014-07-01</p> <p>>> how the component is to be used:In the production of acetic anhydride and acetic acid.</p> <p>>> any trade name for it:Methanol.</p> <p>>> the manufacturing process being used:Acetic Acid is produced by the carbonylation of methanol, i.e. reacting methanol with carbon monoxide at high temperature and pressure in the presence of a catalyst. Acetic Anhydride is produced by the carbonylation of methyl acetate, i.e reacting methyl acetate with carbon monoxide (the methyl acetate being produced by reacting methanol with acetic acid) at high temperature and</p>

ex 2909 60 00	20	329376/2011	<p>1,4-Di(2-<i>tert</i>-butylperoxyisopropyl)benzene (CAS RN 2781-00-2) or mixture of isomers 1,4-Di(2-<i>tert</i>-butylperoxyisopropyl)benzene and 1,3-di(2-<i>tert</i>-butylperoxyisopropyl)benzene (CAS RN 25155-25-3) FR 14.09.2016</p> <p>1,4-Di(2-<i>tert</i>-butylperoxyisopropyl)benzene (CAS RN 25155-25-3)</p>	S	Amendment	<p>pressure in the presence of a catalyst. >> relevant chemical or physical characteristics:Highly volatile and flammable, colourless liquid and vapour, toxic, distinctive alcohol odour. >> what the finished product is:Acetic acid and acetic anhydride</p> <p>ROUND 2017-07 amending request Prolongation Exercise 2017-01-01</p>
ex 3204 16 00	20	779822/2014	<p>PT proposal: Preparations based on colorant reactive black 5 (CAS RN 17095-24-8) containing 60 % or more by weight of this colorant, whether including or not, one or more of the following:- Colorant Reactive Yellow 201 (CAS RN 27624-67-5), - 1-Naphthalenesulphonicacid,4-amino-3-[[4-[[2-(sulphooxy)ethyl]sulphonyl]phenyl]azo]-, disodium salt (CAS RN 250688-43-8), or - 3,5-diamino-4-[[4-[[2-(sulphooxy)ethyl]sulphonyl]fenyl]azo]-2-[[2-sulfo-4-[[2-(sulphooxy)ethyl]sulfonyl]phenyl]azobenzoic acid sodium salt (CAS RN 906532-68-1)</p> <p>Colourant Reactive Black 5 (CAS RN 17095-24-8) and preparations based thereon with a colourant Reactive Black 5 content of 60 % or more but not more than 75 % by weight, and</p>	S	Amendment	<p>ROUND 2017 07 amending request</p> <p>ROUND 2016 07: objection ROUND 2016 01:request for an amendment</p> <p>ROUND 2015-01-01 Reactive dye used in the manufacture of textiles / garments</p>

ex 3811 21 00	57	827236/2014	<p>including one or more of the following:</p> <ul style="list-style-type: none"> - Colourant Reactive Yellow 201 (CAS RN 27624-67-5), - 1-Naphthalenesulphonicacid,4-amino-3-[[4-[[2-(sulphooxy)ethyl]sulphonyl]phenyl]azo]-, disodium salt (CAS RN 250688-43-8), or - 3,5-diamino-4-[[4-[[2-(sulphooxy)ethyl]sulphonyl]feryl]azo]-2-[[2-sulfo-4-[[2-(sulphooxy)ethyl]sulfonyl]phenyl]azobenzoi c acid sodium salt (CAS RN 906532-68-1) <p>Additives containing:</p> <ul style="list-style-type: none"> - a polyisobutylene succinimide based mixture, and - more than 30 % but not more than 50 % by weight of mineral oils, <p>having a total base number of more than 40, for use in the manufacture of lubricating oils FR 14.09.2016</p> <p>Additives containing:</p> <ul style="list-style-type: none"> - a polyisobutylene succinimide based mixture, and - more than 40 % but not more than 50 % by weight of mineral oils, <p>having a total base number of more than 40, for use in the manufacture of lubricating oils</p>	S	Amendment	<p>ROUND 2017-07 amending request</p> <p>ROUND 2015-01 The product is a polyolefin imide alkylene polyamine which is further reacted boric acid and terephthalic acid. It is a dispersant for automatic transmission fluids to prevent sludge and deposits</p>
3824 90 96		1268378/2016	<p>Revised text by the applicant</p> <p>Mixture with a non-stoichiometric composition:</p> <ul style="list-style-type: none"> - with a crystalline structure, - with a content of fused magnesia-alumina 	S	Amendment	<p>ROUND 2017-07 rollover request</p> <p>ROUND 2017 01: The material being the subject of this application is used in the production technologies of</p>

			<p>spinel and with admixtures of silicate phases and aluminates, at least 75 % by weight of which consists of fractions with a grain size of 1-3 mm and at most 25 % consists of fractions with a grain size of 0-1 mm</p> <p>Mixture with a non-stoichiometric composition:</p> <ul style="list-style-type: none"> - with a crystalline structure, - with a dominating participation of magnesia-alumina spinel and with admixtures of silicate phases and aluminates, at least 75 % by weight of which make fractions with a grain size of 1-3 mm and at most 25 % make fractions with a grain size of 0-1 mm 			<p>unburned magnesia-spinel-carbon refractory bricks and burned magnesia-spinel bricks employed in high-temperature processes in the industrial production</p>
ex 3824 99 92	21	3675457/2015	<p>Solution of 2-chloro-5-(chloromethyl)-pyridine (CAS RN 70258-18-3) in organic diluent DE 12.09.2016</p> <p>Solution of 2-chloro-5-(chloromethyl)-pyridine (CAS RN 70258-18-3) in Toluene</p>	S	Amendment	<p>HS 2016 3824 90 92 --> 3824 99 92</p> <p>ROUND 2017-07 amending request</p> <p>ROUND 201607 Intended use:Plant protection active substance</p>
ex 3824 99 92	24	1367671/2016	<p>Mixture containing two or more of the following acrylates;</p> <ul style="list-style-type: none"> - urethane acrylates, - tripropylene glycoldiacrylate, - ethoxylated bisphenol A acrylate or - poly(ethyleneglycol) 400 diacrylate 	S	Amendment	<p>ROUND 2017 07 OBJECTION ROUND 2017 01:This raw material is used in inks, coatings and adhesives, for the printing & packaging and wood industry.</p> <p>HS 2016 3824 90 92 --> 3824 99 92</p>

ex 3913 90 00	92	768/05	<p>BE proposal: Protein, chemically or enzymatically modified by carboxylation and/or phthalic acid addition and/or hydrolysis, having a weight average molecular weight (M_w) of less than 350 000</p> <p>Protein, chemically modified by carboxylation and/or phthalic acid addition, having a weight average molecular weight (M_w) of 100 000 to 300 000</p>	S	Amendment	<p>ROUND 2017-07 amending request</p> <p>Prolongation Exercise 1/1/2014</p>
ex 3920 20 29	60	1154/2008	<p>Mono-axial oriented film, of a total thickness of not more than 75 µm, consisting of two or three layers, each layer containing a mixture of polypropylene and polyethylene, with a core layer whether or not containing titanium dioxide, having:</p> <ul style="list-style-type: none"> - a tensile strength in the machine direction of 140 MPa or more but not more than 270 MPa and - a tensile strength in the transverse direction of 20 MPa or more but not more than 40 MPa <p>as determined by test method ASTM D882/ISO 527-3</p>	S	Amendment	<p>ROUND 2017-07 objection</p> <p>Prolongation Exercise 1/1/2014</p>
ex 3920 20 29	70	1176/2009 461/7/1999 PROLONG 2015	<p>Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, with a core layer whether or not containing titanium dioxide, having:</p> <ul style="list-style-type: none"> - a thickness of 55 µm or more but not more than 97 µm, - a tensile modulus in the machine direction 	S	Amendment	<p>ROUND 2017 07 OBJECTION</p> <p>ROUND 2017 01:measure opposed</p> <p>Prolongation Exercise 2015-01-01</p>

<p>ex 7410 11 00 ex 8507 90 80 ex 8545 90 90</p>	<p>10 60 30</p>	<p>328894/2011</p>	<p>of 0,30 GPa or more but not more than 1,45 GPa, and - a tensile modulus in the transverse direction of 0,20 GPa or more but not more than 0,70 GPa</p>	<p>S</p>	<p>Amendment</p>	<p>prolongation exercise 1.1.2017</p> <p>ROUND 2017-07 amending request</p>
<p>ex 7607 19 90 ex 8507 90 80</p>	<p>10 80</p>	<p>328900/2011</p>	<p>Roll of laminate foil of graphite and copper, with: - a width of 610 mm or more but not more than 620 mm, and - a diameter of 690 mm or more but not more than 710 mm, for use in the manufacture of lithium-ion electric batteries UK 03.06.2019</p> <p>Roll of laminate foil of graphite and copper, with: - a width of 610 mm or more but not more than 620 mm, and - a diameter of 690 mm or more but not more than 710 mm, for use in the manufacture of lithium-ion electric vehicle batteries</p>	<p>S</p>	<p>Amendment</p>	<p>prolongation exercise 1.1.2017</p> <p>ROUND 2017-07 amending request</p>

ex 8108 90 50	25	982750/2011	<p>Sheet in the form of a roll consisting of a laminate of lithium and manganese bonded to aluminium, with:</p> <ul style="list-style-type: none"> - a width of 595 mm or more but not more than 605 mm, and - a diameter of 690 mm or more but not more than 710 mm, <p>for use in the manufacture of cathodes for lithium-ion electric vehicle batteries</p>	S	Amendment	<p>ROUND 2017-07 amendment request</p> <p>ROUND 2017 01:amending request referring to description "Strip of an titanium alloy"</p> <p>for spectacle frames and mountings</p>
8407 33 20 8407 33 80		1272671/2016	<p>4.6.2016 PL proposal: Single cylinder, four stroke internal combustion spark-ignition engine</p> <ul style="list-style-type: none"> - with a cylinder capacity of more than 325 cm³ but not more than 570 cm³, - with overall dimensions of not more than 320 mm (length) x 381 mm (width) x 550 mm (height), - a power of more than 22kW but not more than 35kW, and - equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree) <p>for use in the manufacture of all-terrain vehicles and utility task vehicles</p>	S	Amendment	<p>ROUND 2017-07 resubmission</p> <p>ROUND 2017-01 The component in question is designated for use in ATV vehicles (All-Terrain Vehicles) and UTV vehicles (Utility Terrain Vehicles). The engine creates the torque, which once it is transferred to the wheels, builds up the progressive speed.</p>

<p>8407 33 80 8407 34 10 8407 34 91</p>		<p>1272702/2016</p>	<p>Single cylinder, four stroke internal combustion spark ignition engine with a cylinder capacity of more than 325 cm³ but not more than 570 cm³,</p> <ul style="list-style-type: none"> - with overall dimensions of not more than 320 mm (length) x 381 mm (width) x 550 mm (height), - a power of more than 22 kW but not more than 35 kW, and - equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree) <p>4.6.2016 PL proposal: Single cylinder, four stroke internal combustion spark-ignition engine with a cylinder capacity of more than 325 cm³ but not more than 570 cm³,</p> <p>— with overall dimensions of not more than: 320 mm (length) x 381 mm (width) x 550 mm (height), — a power of more than 22kW but not more than 35kW, — equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree) for use in the manufacture of all-terrain vehicles (ATV) and utility task vehicles (UTV – side by side)</p> <p>Dual cylinder, four stroke internal combustion spark ignition engine with a cylinder capacity of more than 850 cm³ but not more than 1200 cm³,</p> <ul style="list-style-type: none"> - with overall dimensions of not more than 350 mm (length) x 480 mm (width) x 560 mm (height), - a power of more than 44 kW but not more 	<p>S</p>	<p>Amendment</p>	<p>ROUND 2017-07 resubmission</p> <p>ROUND 2017-01 The component in question is designated for use in ATV vehicles (All-Terrain Vehicles) and UTV vehicles (Utility Terrain Vehicles).</p>
-------------------------------------------------	--	---------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------	-------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<p>ex 8409 91 00 ex 8409 99 00 ex 8411 99 00</p>	<p>65 30 70</p>	<p>371591/2013</p>	<p>than 130 kW, and - equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree) or ended with a boss</p> <p>Spiral-shaped gas turbine turbocharger component: - with a heat-resistance of not more than 1050 °C, - with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, - whether or not with an engine exhaust manifold</p>	<p>S</p>	<p>Amendment</p>	<p>SUS 2015-07 change request</p> <p>ROUND 2014-01-01: The turbine housing is a component of the turbocharger. The turbine housing transports the air to the turbine wheel, while increasing its energy through the spiral shape</p>
<p>ex 8501 10 10</p>	<p>20</p>	<p>3869594/2015</p>	<p>Synchronous motor for a dishwasher with a water flow control mechanism with - a length without axle of 24 mm (+/- 0,3), - a diameter of 49,3 mm (+/- 0,3), - a rated voltage of 220 V AC or more but not more than 240 V AC, - a rated frequency of 50 Hz or more but not more than 60 Hz, - an input power of not more than 4 W, - a rotation speed of 4 rpm or more but not more than 4,8 rpm, - an output torque of not less than 10 kgf/cm PL 03.09.2016</p> <p>Synchronous motor for a dishwasher with a water flow control mechanism with - a length without axle of 24 mm (+/- 0,3), - a diameter of 49,3 mm (+/- 0,3)</p>	<p>S</p>	<p>Amendment</p>	<p>ROUND 2017-07 amendment request SUS 2016 07 Permanent magnetized synchronous motor of an output power not exceeding 18W, propelling water flow control mechanism used in dishwashers, having specially designed output shaft, enabling direct cooperation with the transmission located in the water flow control mechanism.</p>

ex 8501 10 99	55	3893585/2015	<ul style="list-style-type: none"> - a rated voltage of 220 V AC or more but not more than 240 V AC, - a rated frequency of 50 Hz or more but not more than 60 Hz, - an input power of not more than 4 W, - a rotation speed of 4rpm or more but not more than 4,8rpm, - an output torque of not more than 10kgf/cm <p>NL proposal:Electric turbocharger actuator, with:</p> <ul style="list-style-type: none"> - a DC motor, - an integrated gear mechanism, - a (pulling)force of 200 N or more at a minimum of 140 °C elevated ambient temperature, - a (pulling) force of 250 N or more in each position of its stroke, - an effective stroke of 15 mm or more but not more than 25 mm, - with or without an on-board diagnostics interface <p>Electric turbocharger actuator, with:</p> <ul style="list-style-type: none"> - a DC motor with an output of 10W or more but not more than 15W, - an integrated gear mechanism, - a (pulling)force of 250N or more at 160°C elevated ambient temperature, - a (pulling) force of 250N or more in each position of its stroke, - an effective stroke of 15mm or more but not more than 20 mm, - with or without an on-board diagnostics interface 	S	Amendment	<p>ROUND 2017-07 amending request</p> <p>SUS 2016 07 Electric Actuator is the actuating component of a regulation. Being part of a fixed geometry turbocharger, the electric actuator adjusts the opening angle of a waste gate valve.</p>
---------------	----	--------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---	-----------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

ex 8505 11 00	33	2520/3/2004 873/2005	<p>Permanent magnets consisting of an alloy of neodymium, iron and boron, either in the shape of a rectangle, whether or not rounded, with a rectangular or a trapezoidal section having</p> <ul style="list-style-type: none"> - a length of not more than 140 mm, - a width of not more than 90 mm and - a thickness of not more than 55 mm, <p>or in the shape of curved rectangle (tile type) having</p> <ul style="list-style-type: none"> - a length of not more than 75 mm, - a width of not more than 40 mm, - a thickness of not more than 7 mm and - a radius of curvature of more than 86 mm but not more than 241 mm <p>or in the shape of a disc with a diameter of not more than 90 mm, whether or not containing a hole in the centre. FR 14.09.2016</p> <p>Permanent magnets consisting of an alloy of neodymium, iron and boron, either in the shape of a rounded rectangle with</p> <ul style="list-style-type: none"> - a length of not more than 90 mm, - a width of not more than 90 mm and - a height of not more than 55 mm, <p>or in the shape of a disc with a diameter of not more than 90mm, whether or not containing a hole in the centre</p>	S	Amendment	<p>ROUND 2017-07 amending request</p> <p>ROUND 2015-01: Amending request</p> <p>Prolongation Exercise 1/1/2014</p>
ex 8505 11 00	45	816924/2014	<p>A quarter sleeve intended to become permanent magnet after magnetization,</p> <ul style="list-style-type: none"> - consisting of at least neodymium, iron and boron, - with a width of 9,1 mm or more but not more than 10,5 mm, - with a length of 20 mm or more but not more than 30,1 mm, <p>of a kind used on rotors for the manufacture of fuel pumps.</p>	S	Amendment	<p>ROUND 2017-07 amendment request</p> <p>ROUND 2015-01 Articles (neodymium magnets) which are subject of this application are used for production of rotors which, in turn, are an integral part of the fuel pump.</p>

ex 8505 11 00	50	312921/2012	<p>PL 13.09.2016</p> <p>A quarter sleeve, intended to become permanent magnet after magnetisation,</p> <ul style="list-style-type: none"> - consisting of at least neodymium, praseodym, iron, boron, dysprosium, aluminium and cobalt, - with a width of 9,2 mm (- 0,1) - with a length of 20 mm (+0,1) or 30 mm (+ 0,1) <p>of a kind used on rotors for the manufacture of fuel pumps</p> <p>PL change request:</p> <p>A quarter sleeve, or a quarter sleeve with chamfered longitudinal edges, intended to become permanent magnets after magnetization,</p> <ul style="list-style-type: none"> - consisting of at least neodymium, holmium, dysprosium, boron and iron, - with a width of 10,4 mm (+/- 0,1 mm) or 9,2 mm (- 0,1 mm), - with a length of 20 mm (+ 0,1 mm) or 30 mm (+ 0,1 mm) <p>of a kind to be used in the manufacture of fuel pumps</p> <p>Bars specifically shaped, intended to become permanent magnets after magnetisation, containing neodymium, iron and boron, with dimensions:</p> <ul style="list-style-type: none"> - a length of 15 mm or more but not more than 52 mm, - a width of 5 mm or more but not more than 42 mm, <p>of a kind to be used in the manufacture of</p>	S	Amendment	It is intended to be incorporated into electrical motors designed for industrial automation
---------------	----	-------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---	-----------	---------------------------------------------------------------------------------------------

ex 8507 90 80	70	328918/2011	<p>electric servomotors for industrial automation</p> <p>Cut plate of nickel-plated copper foil, with:</p> <ul style="list-style-type: none"> - a width of 70 mm (\pm 5 mm), - a thickness of 0,4 mm (\pm 0,2 mm), - a length of not more than 55 mm, <p>for use in the manufacture of lithium-ion electric batteries</p> <p>UK 13.09.2016</p> <p>Cut plate of nickel-plated copper foil, with:</p> <ul style="list-style-type: none"> - a width of 70 mm (\pm 5 mm), - a thickness of 0,4 mm (\pm 0,2 mm), - a length of not more than 55 mm, <p>for use in the manufacture of lithium-ion electric vehicle batteries</p>	S	Amendment	<p>ROUND 2017-07 amending request</p> <p>prolongation exercise 1.1.17</p> <p>TARIC code 7410 22 00 10 to be deleted by 31.12.12</p>
ex 8522 90 80	30	277185/2011	<p>Metal holder, metal fixing item or internal stiffener of metal, for use in the manufacture of televisions, monitors and video players</p> <p>SK 12.09.2016</p> <p>Holder, fixing item or internal stiffener of metal, for use in the manufacture of televisions, monitors and video players</p>	S	Amendment	<p>ROUND 2017-07 amending request</p> <p>prolongation exercise 1.1.17</p> <p>1.1.17 8529 90 92 30 deleted as duty free via ITA</p>
ex 8529 90 92	36	1093297/2015	<p>LCD module</p> <ul style="list-style-type: none"> - with a diagonal measurement of the screen of 14,5 cm or more but not more than 38,5 cm, - straight or curved, - with or without a touch screen, - with an LED backlight, 	S	Amendment	<p>ROUND 2017-07 amending request</p> <p>SUS 2016 07 - end use ought to be implemented</p>

ex 8544 20 00	20	1233197/2015	<ul style="list-style-type: none"> - with a CAN (Controller area network)-controller with one or more LVDS (Low-voltage differential signalling) interfaces and one or more CAN/power supply sockets or with an APIX (Automotive Pixel Link) controller with APIX interface, - in a housing with or without a heat sink at the back of the housing, - without a signal-processing module, - whether or not with haptic and acoustical feedback, <p>for use in the manufacture of vehicles of chapter 87 DE 12.09.2016</p> <p>Colour LCD display panel for LCD monitors of heading 8528:</p> <ul style="list-style-type: none"> - with a diagonal measurement of the screen of 14,48 cm or more but not more than 31,24 cm, - with backlight, micro-controller, - with a CAN (Controller area network)-controller with LVDS (Low-voltage differential signalling) interface and CAN/power supply socket or with an APIX (Automotive Pixel Link) controller with APIX interface, - in a housing with or without a heat sink at the back of the housing, - without a signal-processing module, <p>for use in the manufacture of vehicles of chapter 87</p>	S	Amendment	ROUND 2017-07 amending request
ex 8544 20 00	20	1233197/2015	<p>Antenna connecting cable for the transmission of analogue radio (AM/FM) and GPS signals, containing:</p> <ul style="list-style-type: none"> - coaxial cable, 	S	Amendment	ROUND 2017-07 amending request

			<ul style="list-style-type: none"> - two or more connectors, - 3 or more plastic clips for attachment to the dashboard <p>of kind used in the manufacture of goods of Chapter 87 SK 12.09.2016</p> <p>Antenna connecting cable for the transmission of analogue radio (AM/FM) and GPS signals, containing:</p> <ul style="list-style-type: none"> - a coaxial cable, - two or more connectors, - 3 or more plastic clips for attachment to the dashboard <p>of kind used in the manufacture of goods of Chapter 87</p>			<p>ROUND 2017 01 amending request in terms of wording</p> <p>ROUND 01-2016 After being assembled, the dashboard will be installed to a passenger car</p>
ex 8548 90 90	48	3117/10/2004	<p>Optical unit, containing at least</p> <ul style="list-style-type: none"> - a laser diode and a photodiode operating at a typical wavelength of 635 nm or more but not more than 815 nm - an optical lens - a "Recording Photodetector Integrated Circuit" (PDIC) - a focussing and tracking actuator 	S	Amendment	<p>ROUND 2017 01 re-shape of goods description most likely necessary (following the discussion in previous cycle)</p> <p>Prolongation Exercise 1/1/2014</p>
ex 8708 30 91	30	3033537/2014	<p>Body of disc type brake in BIR ("Ball in Ramp"), EPB ("Electronic Parking Brake") version or in version with hydraulic function only, containing functional and mounting openings and guide grooves, of a kind used in the manufacture of goods of Chapter 87 DE 12.09.2016</p> <p>Body of disc type brake in BIR ("Ball in Ramp")</p>	S	Amendment	<p>ROUND 2017-07 amending request</p> <p>SUSP 2015-07 The body of disc type brake is part of the brake caliper which is subsequently mounted on the rear chassis of the passenger car.</p>

ex 8708 40 20 ex 8708 40 50	20 10	3883567/2015	or EPB ("Electronic Parking Brake") version containing functional and mounting openings and guide grooves, of a kind used in the manufacture of goods of Chapter 87	S	Amendment	ROUND 2017-07 amending request
			Automatic hydrodynamic gearbox - with a hydraulic torque converter - without transfer box and cardan shaft - with or without front differential for use in the manufacture of motor vehicles of Chapter 87 DE 12.09.2016			ROUND 201607 The automatic gearbox subsequently assembled and mounted on the drive mechanism of the vehicle using hydraulic platform jacks and electric hoists
ex 9001 50 41 ex 9001 50 49	30 30	825118/2014	Automatic hydrodynamic gearbox with a hydraulic torque converter without transfer box, cardan shaft and front differential for use in the manufacture of motor vehicles of Chapter 87	S	Amendment	ROUND 2017-01 Goods description again to be discussed ROUND 2015-01-01 The product is an ophthalmic lens for glasses adaptable to the vision correction of the wearer, worked on both surfaces, receiving the appropriate treatments and having to be adapted on a pair of glasses.
			Round organic uncut corrective eyeglass lens blanks, finished on both sides: - of a diameter of 4,9 cm or more but not more than 8,2 cm, - of a height of 0,5 cm or more but not more than 1,8 cm, measured when the lens is laid on a flat surface from the horizontal plane to the lens front surface centre of a kind used to be processed in order to be adapted to a pair of glasses			

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)